

Verbeterblad voor HP1 bij BaZ nr 037b/22. Verwijder volledige inhoud van pagina 254 en vervang door:
 Block for HP1 to NL Ntm 037b/22. Delete content of page 254 and replace by:

IJmuiden Locks - Noordersluis				
Dimensions Locks	Length	Width	Navigable depth	
	400m	50m	14m	
Maximum vessel dimensions	Length	Beam	Draught	UKC
	325m	42m	131dm	≥1m
Under certain conditions (= combination of draught, beam, E-going or W-going and weather) vessels may exceed the maximum dimensions allowed when permission is granted by the harbour master. Request for exemptions are to be forwarded, via www.portofamsterdam.com , 3 days in advance of the estimated time of passage through Noordersluis.				
Visibility	At least twice the vessels length plus 200m			
Max. windforce	5 Bft crosswind			
Tugboat assistance	<ul style="list-style-type: none"> ■ Available; ■ All tankers loaded with inflammable liquids or gasses included vessels when empty and not gas-free unless they are provided with an inert atmosphere are compulsory to make use of tugboats; ■ Vessels with a controllable pitch propeller, azi- and fixed pods, diesel electric propulsion or with a gearbox are exempt from the obligation to make use of the assistance of a tugboat. 			
Boatmen assistance	available			
Note	For communication with locks see section 11.4.4.4 'Communication locks'.			

IJmuiden Locks - Zeesluis IJmuiden				
Dimensions Locks	Length	Width	Navigable depth	
	545m	70m	16.8m	
Maximum vessel dimensions	Length	Beam	Draught	
	398m	57m	137.5dm	
Visibility	At least twice the vessels length plus 200m			
Max. windforce	5 Bft crosswind			
Tugboat assistance	<ul style="list-style-type: none"> ■ All tankers loaded with inflammable liquids or gasses included vessels when empty and not gas-free unless they are provided with an inert atmosphere are compulsory to make use of tugboats; ■ Vessels >175m are compulsory to make use of a stern and front tugboat; ■ Vessels with a controllable pitch propeller, azi- and fixed pods, diesel electric propulsion or with a gearbox are exempt from the obligation to make use of the assistance of a tugboat. 			
Boatmen assistance	available			
Note	For communication with locks see section 11.4.4.4 'Communication locks'.			

11.6.4.2 Amsterdam

Oranjesluizen (4 locks)	
Maximum Ship's dimensions	Up to the lock master
Remarks	<ul style="list-style-type: none"> ■ Operational: 24h; ■ Contact: see caution 11.4.4.4 'Communication with locks'; ■ When the difference in water level of inner IJ and outer IJ is more than 1.45m the locks are not operational.